



CITY BUS



Technical Offer: <u>XML6125J13C - (32+1+4deployable+80 Standing)</u>

SYSTEM	PART NAME	DESCRIPTION	
GENERAL	Overall Dimension -	11980× 2540 × 3150 mm	
	L×W×H		
	Wheelbase	6100 mm	
	Fuel Tank Capacity	200 L with lockable fuel cap	
	Max Speed	>=100Km/h	
	Seat Capacity	(32+1+4deployable+80 Standing) -117 Seater)	
	Engine	CUMMINS ISLe 310 31(EURO III),	
CHASSIS		Displacement: 8.9L, six cylinder, 4cycle diesel engine, Turbocharged. Max power:228kW/2200rpm,	



	Max torque:1200 N.m/1000-1500rpm
Clutch	Chinese brand, dry type, Φ430
clutch booster	WABCO , dry type torque 1200N.m, friction diameter 430mm, hydraulic
Transmission+ Reta	rder QJS6-90,manual, six gears, with electr omagnetic retarder – ZF Technology
Front axle	Chinese, 6500 Kg, with anti-roll bar, heavy duty I-beam
Rear axle	Chinese , 13000Kg, fully floating ,single speed
Suspension	Leaf spring, ZF shock absorber
Steering wheel	Hydraulic power assisted
Tyre	275/70R22.5,radial tubeless tire
Spare tyre	Equipped
Brake system	Drum type, dual line full air brake with exhaust brake, spring actuated parking brake acting on rear wheels.
Air dryer	WABCO
ABS & Auto slack a	adjuster WABCO ABS + HEDLEX auto slack adjuster
Engine compartme insulation treatment	
Variable speed conselection device	ntrol for Two flexible shaft control
Towing devices	Front and rear
Engine exhaust brak	ke Equipped
Engine exhaust orak	te Equipped



W i	
M.	

BODY	Floor	Flat floor	
	Painting	Standard paint (Determined by purchaser)	
	Driver seat	Air suspension, leather, adjustable, three-point belts	
	Passenger Seat	(32passenger +1driver +4deployable +80 Standing) -117 Seater)	
	Passenger belt	Equipped	
	Trim of roof	PVC panel	
	Front sunshade curtain	Two adjustable pieces	
	Top hatch	Two, with 4 ventilators	
	Dashboard	City bus dashboard	
	Door Emergency valve	Equipped	
	Middle Door	Dual swing-in door	
	Rear door	Dual swing-in door	
	Driver door	Equipped	
	Rear engine compartment door	Over-flapping aluminum alloy luggage door	
	Front windshield	Two pieces	
	Driver Window	Manual driver tempered glass	
	Side window	Sliding windows, with guardrail	
	Floor Material	15mm bamboo floor	
	Outside Rearview Mirror	Manual bracket, left right short long	
	Emergency Hammer	6 units	



4	N	
1		
1,00	u	ı

Air intake	Rear side wall intake
Fire Extinguisher	2*2KG
Engine fire extinguishing device	Equipped
Side compartment door	Over-flapping aluminum alloy luggage door
Driver's Side window curtain	Driver's window curtain hanging strip
Side window decoration	Extrusion molding
Side wall decoration	PVC board Light color cladding
Floor carpet	Gray colored, door opening area with yellow colored, disabled area with blue colored
Guard rail	Front door guardrail +middle door guardrail+ rear door guardrail +side window guardrail+ roof guardrail
Driving cab	Guard rail, PP board
Driving habit	LHD
Wheelchair fixing mechanism	Equipped
Electric ramp for wheelchair	Equipped
Seat number	Equipped
Interior rear mirror	Equipped
Appearance	MAN appearance
Standing passenger armrest	Equipped



4	N	
1		
1,00	u	ı

	Bumper	Front & rear equipped	
ELECTRICAL EQUIPMENT	Driver's fan	Equipped	
	Top lights	8 square lamps	
	High position brake lamp	Equipped	
	Inside audio horn	6 units	
	Inside audiovisual system	DVD player with radio, with microphone	
	Driver micro phone	Equipped	
	Front Display	19 inch LCD (fixed)	
	Reversing monitor	Color reversing monitor	
	Monitor system	Total 5 , front door+middle door+rear door+front roof+rear roof with 3200 recorder	
	Digital clock	Equipped	
	Meter	CAN bus instrument	
	Wiper	Front	
	Engine Alternator	Prestolite alternator,90A	
	Battery	2×180Ah	
	Harness specification	125°C harness heat resistance outside and 105°C harness heat resistance inside	
	Tachograph	equipped	
	Emergency flameout switch	Equipped	
	Reversing buzzer	Equipped	



# 0	
1	

		W.
	Get-off ring	Equipped
	Audible warning	Equipped
	Engine fire extinguishing	Equipped
	alarm device	
	Air Condition	Equipped
	Defroster	Front defroster
	Total circuit switch	Equipped
	Electric horn	Equipped
	Engine compartment temperature alarm device	Equipped
	The main lamp (rear wall)	Standard
	The main lamp (front wall)	Standard
Other EQUIPMENT	Grease gun	Equipped
	Jack with wheel wrench	Equipped
	Cigarette lighter	Equipped
	Mud guard, rear	Equipped

Available Optional		
PART NAME	DESCRIPTION	PRICE in USD
Air Condition	DENZO / SONGS – 30,960-34,400kcal/h	
Middle Display	19 inch LCD	





LED Dot matrix	At the front, rear, right side and inside	
Destination Board	Destination reported device for Off-board passenger	

Interior Pictures









